## STANDARD GLT

## CUSTOM-SIZED AND DIMENSIONAL TIMBER

WIEHAG

TYPES OF WOOD:	Spruce, fir (larch, pine, Douglas fir available on request)
LENGTHS:	Dimensional timber up to 24.0 m available Commissioned production of timber in multiple lengths or cut individually to fixed sizes
SPECIAL LENGTHS:	Up to 50.0 m available on request (special transport may be required for 14.0 m and longer)
STANDARD WIDTH:	80 to 260 mm; other widths available on request (in steps of 20 mm)
STANDARD HEIGHT:	Up to 1.2 m; other heights available on request (lamella size: 41 mm)
STRENGTH CATEGORIES:	GL24h, GL28c for an additional charge; other strength categories available on request
SURFACE QUALITY:	Visible, natural and industrial (see GLT fact sheet for detailed description)
SERVICE CLASS:	Service class 1, 2
WOOD MOISTURE CONTENT:	11 ±2.5%
PRODUCTION STANDARD:	EN 14080
BONDING:	MUF type I PEFCG-sa-tea
LAMELLA THICKNESS:	41 mm
PRODUCT LABELLING:	Label on product CE label PEFC and FSC available on request
PACKAGING:	Shrink-wrapped in packs; individually shrink-wrapped on request (additional charge) Our wrapping acts as transport protection. However, it is only suitable to a limited extent as temporary protection from UV radiation and precipitation.
OTHER OPTIONS:	For formed components, see "Beam Shapes" product data sheet. For pre-assembled options, see "Factory Assembly Options" product data sheet.



OVERVIEW OF ALL PRODUCT DATA SHEETS >



FACTORY ASSEMBLY OPTIONS